



SS 20

SILVER / SILVER 20

Visible Light Transmittance (VLT) 20%

UV Rejection (UVR) 75.00%

Infrared Rejection (IRR) 950NM 80%

Infrared Rejection (IRR) 1400NM 85%

Total Solar Energy Rejection (TSER) 52%

Thickness 2MIL



IR durability performance,
colour durability performance

4K CLEAR VISION

BUILDING FILM



SS 05

SILVER / SILVER 05

Visible Light Transmittance (VLT)	5%
UV Rejection (UVR)	80.00%
Infrared Rejection (IRR) 950NM	85%
Infrared Rejection (IRR) 1400NM	90%
Total Solar Energy Rejection (TSER)	65%
Thickness	2MIL



IR durability performance,
colour durability performance

4K CLEAR VISION

BUILDING FILM



SILVER BLACK

SILVER BLACK

Visible Light Transmittance (VLT) 5%

UV Rejection (UVR) 80.00%

Infrared Rejection (IRR) 950NM 85%

Infrared Rejection (IRR) 1400NM 90%

Total Solar Energy Rejection (TSER) 65%

Thickness 2MIL



IR durability performance,
colour durability performance

4K CLEAR VISION

BUILDING FILM



SILVER GREEN

SILVER GREEN

Visible Light Transmittance (VLT)	20%
UV Rejection (UVR)	80.00%
Infrared Rejection (IRR) 950NM	65%
Infrared Rejection (IRR) 1400NM	70%
Total Solar Energy Rejection (TSER)	48%
Thickness	2MIL



IR durability performance,
colour durability performance

4K CLEAR VISION

BUILDING FILM