



KCP 7095

Visible Light Transmittance (VLT)	70%
UV Rejection (UVR)	99.00%
Infrared Rejection (IRR) 950NM	92%
Infrared Rejection (IRR) 1400NM	98%
Total Solar Energy Rejection (TSER)	57%
Thickness	2 MIL

KOREAN CHAMELEON PURPLE

9K CLEAR VISION



IR durability performance,
colour durability performance



KKP 7095

Visible Light Transmittance (VLT)	70%
UV Rejection (UVR)	99.00%
Infrared Rejection (IRR) 950NM	92%
Infrared Rejection (IRR) 1400NM	98%
Total Solar Energy Rejection (TSER)	57%
Thickness	2 MIL

KOREAN KING PURPLE

9K CLEAR VISION



IR durability performance,
colour durability performance



KCR 8080

Visible Light Transmittance (VLT)	80%
UV Rejection (UVR)	99.00%
Infrared Rejection (IRR) 950NM	75%
Infrared Rejection (IRR) 1400NM	80%
Total Solar Energy Rejection (TSER)	44%
Thickness	2 MIL

KOREAN CHAMELEON RED

9K CLEAR VISION



IR durability performance,
colour durability performance



KCR 7095

Visible Light Transmittance (VLT)	70%
UV Rejection (UVR)	99.00%
Infrared Rejection (IRR) 950NM	92%
Infrared Rejection (IRR) 1400NM	98%
Total Solar Energy Rejection (TSER)	54%
Thickness	2 MIL

KOREAN CHAMELEON RED

9K CLEAR VISION



IR durability performance,
colour durability performance



KCR 3595

Visible Light Transmittance (VLT)	35%
UV Rejection (UVR)	99.00%
Infrared Rejection (IRR) 950NM	91%
Infrared Rejection (IRR) 1400NM	98%
Total Solar Energy Rejection (TSER)	70%
Thickness	2 MIL

KOREAN CHAMELEON RED

9K CLEAR VISION



IR durability performance,
colour durability performance



KCG 7095

Visible Light Transmittance (VLT)	70%
UV Rejection (UVR)	99.00%
Infrared Rejection (IRR) 950NM	92%
Infrared Rejection (IRR) 1400NM	98%
Total Solar Energy Rejection (TSER)	62%
Thickness	2 MIL

KOREAN CHAMELEON GREEN

9K CLEAR VISION



IR durability performance,
colour durability performance



KCB 5095

Visible Light Transmittance (VLT)	60%
UV Rejection (UVR)	99.00%
Infrared Rejection (IRR) 950NM	92%
Infrared Rejection (IRR) 1400NM	98%
Total Solar Energy Rejection (TSER)	65%
Thickness	2 MIL

KOREAN CHAMELEON BLUE

9K CLEAR VISION



IR durability performance,
colour durability performance



KCM 5095

Visible Light Transmittance (VLT)	60%
UV Rejection (UVR)	99.00%
Infrared Rejection (IRR) 950NM	92%
Infrared Rejection (IRR) 1400NM	98%
Total Solar Energy Rejection (TSER)	65%
Thickness	2 MIL

**KOREAN CHAMELEON
MULTI COLOUR**

9K CLEAR VISION



IR durability performance,
colour durability performance



KCM 2095

Visible Light Transmittance (VLT)	20%
UV Rejection (UVR)	99.00%
Infrared Rejection (IRR) 950NM	92%
Infrared Rejection (IRR) 1400NM	98%
Total Solar Energy Rejection (TSER)	75%
Thickness	2 MIL

**KOREAN CHAMELEON
MULTI COLOUR**

9K CLEAR VISION



IR durability performance,
colour durability performance